

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Long Life Lamp Company

Supplier's address: T2 Arundel Rd Uxbridge UB8 2RP UK

Model identifier: BL40CW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	Non-directional
Light source cap-type (or other electric interface)	Built-in		
Mains or non-mains:	Mains	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	40	Energy efficiency class	F
---	----	-------------------------	---

Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4000 in wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6500
---	-----------------------------------	--	------

On-mode power (P_{on}), expressed in W	40	Standby power (P_{sb}), expressed in W and rounded to the second decimal	-
--	----	--	---

Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
--	---	--	----

Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	65	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	1170		
	Depth	72		

Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	333
--	-----	------------------------------	-----

		Chromaticity coordinates (x and y)	0,313 0,337
--	--	------------------------------------	----------------

Parameters for LED and OLED light sources:

R9 colour rendering index value	>1	Survival factor	0,96
---------------------------------	----	-----------------	------

the lumen maintenance factor	$L70 > 30000H$		
------------------------------	----------------	--	--

Parameters for LED and OLED mains light sources:

displacement factor ($\cos \phi_1$)	-	Colour consistency in McAdam ellipses	≤ 6
---------------------------------------	---	---------------------------------------	----------

Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	No	If yes then replacement claim (W)	-
---	----	-----------------------------------	---

Flicker metric (Pst LM)	<0,9	Stroboscopic effect metric (SVM)	<0,4
-------------------------	------	----------------------------------	------

(a) : not applicable;

(b) : not applicable;

